



# ACCESS CONTROL

## HID PROXIMITY CARDS 1326, 1386

1

ACCESS CONTROL

### DESCRIPTION

The **1326 ProxCard II** proximity access card is the industry choice for a cost-effective solution to proximity access control, with universal compatibility with all HID proximity readers. The ProxCard II provides durable packaging and consistent read range. The **1386 ISOProx II** card offers proximity technology with photo identification capability on a single card. It is ISO 7810 compliant, with nominal thickness of 0.03".

### FEATURES

- *Universal compatibility with all HID proximity readers*
- *Durable packaging and consistent read range*
- *External number for easy identification and control*
- *Supports formats up to 85 bits, with over 137 billion codes*
- *Custom pre-printed artwork available*



- *A PVC overlay allows for on-site photo ID using most direct image printers*
- *Thin enough to carry in a wallet or purse*
- *Create Photo ID card with model 1324 Printable Adhesive Label*

### SPECIFICATIONS

<b>Excite Frequency</b>	125 kHz	<b>Operating Temperature</b>	-50° to 160°F (-45° to 70°C)
<b>Read Range</b>		<b>Dimensions</b>	
<b>ProxPoint® Plus reader</b>	up to 3" (7.5 cm)	<b>1326</b>	3.39" H x 2.14" W x 0.08"D (8.6 x 5.4 x 0.19 cm)
<b>MiniProx® Reader</b>	up to 5.5" (14 cm)	<b>1386</b>	3.37" H x 2.12" W x 0.03"D (8.6 x 5.4 x 0.076 cm)
<b>ThinLine® II Reader</b>	up to 5.5" (14 cm)	<b>Weight</b>	0.24 oz (6.8 gm)
<b>ProxPro® Reader</b>	up to 8" (20 cm)		
<b>ProxPro® II Reader</b>	up to 9" (22.9 cm)		
<b>Prox80™ Reader</b>	up to 5.5" (14 cm)		
<b>MaxiProx® Reader</b>	up to 24" (60 cm)		

### ORDERING INFORMATION

MODEL	DESCRIPTION
1326-HID	(1 card) ProxCard® II clamshell card
1386-HID	(1 card) ISOProx II card

## XCEEDID PROXIMITY CARDS 9520

### DESCRIPTION

The **9520** card is similar in size and thickness to traditional credit cards. The reason it is referred to as an ISO card is that its dimensions comply with standards specified in applicable ISO guidelines. The smooth, high-quality surface is ideal for printing of custom artwork, images, and photographs.

### FEATURES

- *Choice of 2.5k, 8k, 10k, or 32k bits of storage to meet the most demanding data storage requirements, including multiple applications and complex biometric templates*
- *Utilizes high-security data which is mutually authenticated in communication between the card and reader, providing an infinite number (many trillions) of unique badge ID codes*
- *Passive design does not require any batteries or maintenance for the life of the card*



### SPECIFICATIONS

<b>Excite Frequency</b>	13.56 MHz
<b>Read Range</b>	
<b>XF 1060 Mini-Mullion</b>	up to 2.5" (6.35 cm)
<b>XF 1100 Mullion</b>	up to 4.5" (11.43 cm)
<b>XF 2100/2110 Mid-Range</b>	up to 6" (15.24 cm)
<b>Operating Temperature</b>	-50° to 160°F (-45° to 70°C)
<b>Dimensions</b>	3.37"H x 2.125"W x 0.033"D (8.56 x 5.4 x .09 cm)
<b>Weight</b>	2.7 oz. (75 gm)

### ORDERING INFORMATION

MODEL	DESCRIPTION
9520	(1 Card) Smart ISO card