



# ELECTRICAL WIRING MATERIALS

## COMPACT SPlicing CONNECTORS 222 SERIES LEVER NUTS

### DESCRIPTION

Compact Splicing Connectors for 2, 3, and 5 conductors.

### FEATURES

- For all connections requiring:
- Stranded/solid wires
- Wide range of wire sizes
- Combination of different wire sizes in one connector
- Small space consumption
- Built-in test point
- Protection against electrical shock, touch safe
- Low installed cost and safe operation
- Maintenance free connection
- Resusable connector



222-412



222-413



222-415



**WAGO**  
INNOVATIVE CONNECTIONS

### SPECIFICATIONS

<b>Voltage Rating</b>	600 V (1000 V signs and fixtures)
<b>Current Rating</b>	20 A maximum
<b>Wire Size</b>	28-12 AWG
<b>Number Of Conductors</b>	2, 3, 5
<b>Operating Temperature</b>	221°F (105°C) maximum
<b>Strip Length</b>	Strip to 0.37" (9-10 mm)

#### Dimensions


<b>222-412</b>	0.81" x 0.49" x 0.57" (2.05 x 1.24 x 1.45 cm)
<b>222-413</b>	0.81" x 0.67" x 0.57" (2.05 x 1.7 x 1.45 cm)
<b>222-415</b>	0.81" x 1.05" x 0.57" (2.05 x 2.66 x 1.45 cm)

#### Approvals


UL Listed E69654

### INSTALLATION


#### Step 1. Strip wire.



#### Step 2. Push up lever.



#### Step 3. Insert conductor and push down lever.



Integrated test port allows for easy testing of connection integrity.

### ORDERING INFORMATION

Model	Number Of Conductors	Description
222-412	2	2 - conductor connector 50 pc box
222-413	3	3 - conductor connector 50 pc box
222-415	5	5 - conductor connector 40 pc box
222-412J	2	2 - conductor connector 350 pc jar
222-413J	3	3 - conductor connector 250 pc jar
222-415J	5	5 - conductor connector 150 pc jar

### ACCESSORIES

**206-124** Wire cutting and stripping tool (34-8 AWG)