

## NON-PLENUM

PART NUMBER	GAUGE SIZE	NO. OF COND.	CONDUCTOR STRAND	JACKET COLOR	NOM. O.D. INCHES	WEIGHT
<b>CATEGORY 3</b>						
W242P-1071	24	2pr	Solid	***	0.13	9 lbs.
W243P-1027	24	3pr	Solid	***	0.15	13 lbs.
W244P-1054	24	4pr	Solid	***	0.16	16 lbs.
W2425P-1070	24	25pr	Solid	***	0.39	105 lbs.

### CATEGORY 5e

W244P-1446	24	4pr	Solid	***	0.20	21 lbs.
------------	----	-----	-------	-----	------	---------

### CATEGORY 6

W244P-1552	23	4pr	Solid	***	0.220	28 lbs.
------------	----	-----	-------	-----	-------	---------

\*\*\* Various colors available. Consult sales office for options.

## DIRECT BURIAL

PART NUMBER	GAUGE SIZE	NO. OF COND.	CONDUCTOR STRAND	JACKET COLOR	NOM. O.D. INCHES	WEIGHT
<b>CATEGORY 5e</b>						
W244P-1897	24	4pr	Solid	Black	0.216	22 lbs.
<b>CATEGORY 6</b>						
W244P-1589	23	4pr	Solid	Black	0.244	30 lbs.

## PLENUM

PART NUMBER	GAUGE SIZE	NO. OF COND.	CONDUCTOR STRAND	JACKET COLOR	NOM. O.D. INCHES	WEIGHT
<b>CATEGORY 3</b>						
W243P-2157	24	3pr	Solid	White***	0.15	13 lbs.
W244P-2027	24	4pr	Solid	White***	0.26	17 lbs.
<b>CATEGORY 5e</b>						
W244P-2175	24	4pr	Solid	Blue***	0.175	21 lbs.
W244P-2176	24	4pr	Solid	White***	0.175	21 lbs.
<b>CATEGORY 6</b>						
W244P-2274	23	4pr	Solid	White***	0.215	28 lbs.

\*\*\* Various colors available. Consult sales office for options.

## Product Construction

**CONDUCTOR:** Solid Bare copper

**INSULATION:**

- Semi-rigid PVC

**JACKET:**

- Premium grade PVC
- Sequential footage markings

**APPLICATION:**

- Voice
- Data

**COMPLIANCES:**

- ANSI/TIA/EIA 568B.2 (Category 3)
- ANSI/ICEA S-90-861 (Category 3)
- ANSI/TIA/EIA-568-B.2 (Category 5e)
- ICEA S-90-861 (Category 5e)
- ICEA S-102-700 (Category 6)
- UL & c(UL) Type CMR

**PACKAGING:**

- 1000 ft. (305m) pay-out cartons
- 1000 ft. (305m) spools or reels

## Product Construction

**CONDUCTOR:** Solid bare copper

**INSULATION:**

- Polyethylene
- Water Block Tape

**JACKET:**

- Low density polyethylene

**APPLICATION:**

- Direct burial
- Outdoor

## Product Construction

**CONDUCTOR:** Solid Bare copper

**INSULATION:**

- FEP

**JACKET:**

- Low smoke flame retardant PVC
- Sequential footage markings

**APPLICATION:**

- Voice
- Data

**COMPLIANCES:**

- ANSI/TIA/EIA 568B.2 (Category 3)
- ANSI/ICEA S-90-861 (Category 3)
- ANSI/TIA/EIA-568-B.2 (Category 5e)
- ICEA S-90-861 (Category 5e)
- ICEA S-102-700 (Category 6)
- ANSI/TIA/EIA-568-B.2-1 (Category 6)
- UL & c(UL) Type CMP

**PACKAGING:**

- 1000 ft. (305m) pay-out cartons
- 1000 ft. (305m) spools or reels