

XCL SERIES SELECTION GUIDE

MODEL	DESCRIPTION		
SPLC	XCL SENSEPOINT CONTROL TRANSMITTER		
	GAS DETECTED		
	A	AMONIA (NH3)	
	C	CARBON MONOXIDE (CO)	
	F	METHANE (CH4)	
	G	HYDROGEN (H2)	
	H	HYDROGEN SULFIDE (H2S)	
	N	NITROGEN DIOXIDE (NO2)	
	O	OXYGEN (O2)	
	RANGE		
	1B	LOW RANGE SENSING	
	2B	HIGH RANGE SENSING	
	6B	FLAMMABLE (CAT)	
	CONTROL SIGNAL		
	A	4-20mA	
	M	MODBUS	
	RELAY OPTION		
	X	STANDARD (NO RELAY)	
	R	RELAY	
	COLOR		
CX	CHARCOAL (STANDARD)		
WX	WHITE		
OPTIONS			
LZZ	CoLA CERTIFIED (ONLY AVAILABLE ON CO 4-20mA MODELS)		
NZZ	STANDARD		

Example:	SPLC	A	1B	A	X	CX	NZZ	SPLCA1BAXCXNZZ	Sensepoint XCL Transmitter, Safe Area, IP65, NH3 (Low Range), 4~20 mA, Charcoal
----------	------	---	----	---	---	----	-----	----------------	---