

HAZARDOUS LOCATIONS

EXPLOSION PROOF HORNS & STROBES

878EX, 879EX, 116EXMST



DESCRIPTION

These Edwards horns and strobes offer a selection that should meet any hazardous location alarming need.

DIVISION 1 & 2 HORNS MODELS 8783X, 879EX

FEATURES

- *Heavy-duty, high-decibel vibrating horn*
- *Corrosion-resistant epoxy finish*
- *NEMA 4X*
- *Wall-mounting with side brackets*
- *Power connection wires embedded in sealing compound*
- *Tapped for 3/4" conduit*
- *97 dB at 10 feet*
- *120 VAC (878EX-N5), 24 VDC @ 160 mA (879EX-G1)*
- *UL listed for Class 1, Divisions 1 and 2, Groups B, C, D; Class II, Divisions 1 and 2, Groups E, F; Class III locations*
- *UL File E14660*



ORDERING INFORMATION

MODEL	DESCRIPTION
878EX-N5	Divisions 1 and 2 horn 120 VAC
879EX-G1	Divisions 1 and 2 horn 24 VDC

DIVISION 1 & 2 STROBE MODEL 116EXMST

FEATURES

- *High-impact glass dome*
- *65 flashes per minute*
- *800,000 peak candlepower*
- *3000-hour lamp rating*
- *NEMA 3R and 4X rated*
- *UL listed 1638, 1203, Marine 1598A; CUL listed C22.2 No. 205; Class I, Division 1, Groups C, D; Class I, Division 2, Groups A, B, C, D; Class II, Division 1, Groups E, F, G; Class II, Division 2, Group F, G; Class III, Division 1, Groups E, F, G; Class III, Division 2, Group G*
- *UL File E212211*



ORDERING INFORMATION

MODEL	DESCRIPTION
116EXMSTR-N5*	Divisions 1 and 2 strobe, red lens 120 VAC
116EXMSTA-N5*	Divisions 1 and 2 strobe, amber lens 120 VAC
116EXMSTB-N5*	Divisions 1 and 2 strobe, blue lens 120 VAC
116-GRD	Optional dome guard
92-ST	Replacement strobe tube
116EX-P	Pendant mount
116EX-B	Wall bracket mount (requires 116EX-C)
116EX-C	Ceiling mount
116EX-S	Stanchion mount

* Requires mount