



MLS Series Multi-level Switch Product Selection Guide

This series of multi-level switch is custom made to application. Please call Kele sales representative at 877-826-9045 and use this guide to specify the requirements for quote.

Pressure, psig: _____

Temperature: _____

Media: _____

Mounting Configuration: **TOP**

1. Series: **MLS**

2. Mounting Type: 1/8" NPT
1/4" NPT
3/8" NPT
1/2" NPT
1" NPT
1 1/4" NPT

3. Stem & Mounting Material: Brass
316SS

4. Float Materials: 316SS
Buna N

5. Wiring Type: SPST Group 1 (Common)
SPST Group 2 (Independent)



MLS Series Multi-level Switch Product Selection Guide

6. Switch Rating: 50 VA SPST

7. Lead Wires: 24"

Note: Lead wire length is 24" if not specified

Cable- Optional

8. Switch Actuation Level:

Actuation Level	Distance to Actuation Level (in Inches*)	SPST Switch Operation**	
		Normally Open	Normally Closed
L6			
L5			
L4			
L3			
L2			
***L1			
****LO			

*Measured from bottom of the mounting plug or flange.

**Switch position is "normal" with the unit dry (empty tank).

***L1 is the distance to the lowest actuation level with mounting "up" and is the distance to the highest actuation level with mounting "down".

****LO = Length overall, measured from the bottom of the mounting plug or flange to the end of the unit.

9. J-Box Option: Standard Pyromation Box

10. Special Requirements: Contact factory