



LEVEL & LEAK DETECTION

LEAK DETECTOR AND ENVIRONMENT MONITOR

F200

DESCRIPTION

The **RLE Technologies Model F200** is an affordable web accessible facility monitoring product that couples leak detection and facility monitoring in one plug-and-play package. Designed to be simple and effective, **RLE Technologies F200** monitors a variety of critical environmental threats and quickly notifies those that can respond.

NEW!



F200



FEATURES

- *Web-accessible with a DHCP or static IP with mobile-friendly web interface screen*
- *Integrated monitoring leak detection device with added eight dry contact inputs, four temperature or temperature/humidity sensors*
- *Alarm notification including audible and visible indicators, integrated web interface, email messaging, and SNMP traps*

- *Relay output upon alarm condition*
- *Modbus TCP IP enabled*
- *Integrated logging and trending with downloadable CSV file*

10

LEVEL & LEAK DETECTION

SPECIFICATIONS

Supply Voltage	5 VDC @ 500 mA max.; 110/240VAC 50/60Hz	Email	1 email recipient; email sent on alarm to single recipient, distribution list, or email-to-SMS
Relay Type	SPDT	SNMP Traps	Multiple community strings
Relay Rating	2 A @ 30 VDC, 0.5 A @ 125 VAC	Security Login	1 password read only, 1 password read/write
Communication Ports	Ethernet 10/100 BaseT, RJ45 connector; 500VAC RMS isolation; DHCP enabled; Static IP-addressable	Altitude Limits	15,000ft (4,572m) max.
Protocols		Operating Humidity	0% to 100% RH, non-condensing
TCP/IP, HTML, SNMP, NTP	V1; V2C MIB-2 compliant; NMS Manageable with Get and Traps	Operating Temperature	-40°F to 185°F (-40°C to 85°C)
SMTP (email)	SMTP authentication; SMTP relay	Mounting	Stand alone; keyholes included for wall mount; rack mount bracket available
Modbus TCP/IP	Modbus slave; TCP/IP transmission protocol	Cable Length	200ft (61m) of conductive fluid sensing cable, or 140ft (43m) of chemical sensing cable
Alarm Panel	Audible alarm, visible LED	Dimensions	5.63"W x 1.00"H x 2.63"D (143mmW x 25mmH x 67mmD)
Integrated Web Interface	Dashboard overview with alarm indicators	Approvals	CE, ETL, CSA, RoHS
		Weight	0.6 lb (0.3 Kg)
		Warranty	1 year

ORDERING INFORMATION

MODEL	DESCRIPTION
F200	Environmental monitor includes 3.3ft (1m) network cable, USB power adapter, and USB mini B to USB A cable

NEW!

602

877-826-9037 USA | kele.com

ONE CALL. ONE INVOICE. ONE SOURCE.

September 2016