

LIGHTING CONTROLS

LIGHTING OVERRIDE SWITCHES

KSW SERIES

DESCRIPTION

The KSW Series (previously LSW) switches are for controlling room and area lighting in commercial applications. The switch actuation on the KSW-T Series is toggle, KSW-P2 Series and the KSW-M are momentary.

FEATURES

- · All models come with cover plates
- Up to 8 momentary switches
- · Available in white, ivory, and stainless steel

SPECIFICATIONS

Contact Rating

Momentary 24 VAC, 3A, Dry Contact

24 VAC/ VDC, 3A,120/ 277 VAC, **Toggle**

15A

Actuation Type Momentary, Toggle Momentary 1, 2, 3, 4, 6, 8


Toggle

Color Ivory, Stainless steel, White




KSW-T-I and KSW-T24-I **Toggle Switches**

KSW-P2-I-11 **Push-button Switch**



KSW-T



KSW-P2

ORDERING INFORMATION

Model	Contact Rating	Number Of Switches	Actuation Type	Color
KSW-P2-I-11	24 VAC, 3A, Dry Contact	2	Momentary	lvory
KSW-P2-I-12	24 VAC, 3A, Dry Contact	4	Momentary	lvory
KSW-P2-I-23	24 VAC, 3A, Dry Contact	6	Momentary	lvory
KSW-P2-I-24	24 VAC, 3A, Dry Contact	8	Momentary	lvory
KSW-P2-S-11	24 VAC, 3A, Dry Contact	2	Momentary	Stainless steel
KSW-P2-S-12	24 VAC, 3A, Dry Contact	4	Momentary	Stainless steel
KSW-P2-S-23	24 VAC, 3A, Dry Contact	6	Momentary	Stainless steel
KSW-P2-S-24	24 VAC, 3A, Dry Contact	8	Momentary	Stainless steel
KSW-P2-W-11	24 VAC, 3A, Dry Contact	2	Momentary	White
KSW-P2-W-12	24 VAC, 3A,Dry Contact	4	Momentary	White
KSW-P2-W-23	24 VAC, 3A, Dry Contact	6	Momentary	White
KSW-P2-W-24	24 VAC, 3A, Dry Contact	8	Momentary	White
KSW-T-I-P	120/ 277 VAC, 15A	1	Toggle	lvory
KSW-T-W-P	120/ 277 VAC, 15A	1	Toggle	White
KSW-T24-W-P	24 VAC/ VDC, 3A	1	Toggle	White
KSW-T24-I-P	24 VAC/ VDC, 3A	1	Toggle	lvory
KSW-M1-I-11	24 VAC/VDC, 4A	1	Momentary	lvory
KSW-M1-I-12	24 VAC/VDC, 4A	2	Momentary	lvory
KSW-M1-I-13	24 VAC/VDC, 4A	3	Momentary	lvory
KSW-M1-W-11	24 VAC/VDC, 4A	1	Momentary	White
KSW-M1-W-12	24 VAC/VDC, 4A	2	Momentary	White
KSW-M1-W-13	24 VAC/VDC, 4A	3	Momentary	White

NEW!