



RR7P / RR7P3

DESCRIPTION

GE RR7PBP and RR7P3 relays are mechanical latching-type devices for direct plug-in to the appropriate GE Lighting Automation Panel.

The RR7PBP has a 5-pin plug-in connector for use with LightSweep panels and frames.
 The RR7P3 relay has a 3-pin plug-in connector.

The three wire dual coil relay requires only momentary 24 volt rectified AC switch circuit pulses to open or close line voltage circuits. Coil design resists burnout that could occur if equipment or operational failure energizes the relay for an extended period of time. All GE low voltage relays may be used to full rated capacity for tungsten filament, ballast or resistive loads.

SPECIFICATIONS

Description	3-Wire Latching Relay with Plug in Connector
Catalog #	Connector
RR7PBP	5-pin
RR7P3	3-pin
Operating Environment	0-60 Degrees C (32-140 F) 10-95% RH, Non Condensing Non corrosive atmosphere Non explosive atmosphere
Rated Capacity	
Lamp Load	20 amp Tungsten Filament 125VAC 30 amp Ballast 277/347 VAC
Resistive Load	30 amp 277/347 VAC
Motor Load	1/2 HP @ 110-125 VAC 1 1/2 HP @ 347 VAC
Codes	UL Listed, CSA Certified