



FUSIBLE STARTER ORDERING INFORMATION/SPECIFICATION TABLE

Part Number	HP	Voltage	Coil Voltage	Enclosure NEMA Rating	Coil Inrush	Coil Holding Current	Overload Range	Fuse Block Rating	Dimensions	Weight
FCXLS7K-1G-O-M01-HOA-PL	5	200/230	24VAC	1	45 VA	6 VA	14.5-18	30A	12" x 10" x 6"	18lbs
FCXLS7K-1G-O-M4-HOA-PL		200/230		12/4		6 VA	14.5-18	30A	12" x 10" x 6"	18lbs
FCXLS7K-1A-O-M01-HOA-PL		200/230	120VAC	1		6 VA	14.5-18	30A	12" x 10" x 6"	18lbs
FCXLS7K-1A-O-M4-HOA-PL		200/230		12/4		6 VA	14.5-18	30A	12" x 10" x 6"	18lbs
FCXLS7K-2G-O-M01-HOA-PL	10	460	24VAC	1	45 VA	6 VA	14.5-18	30A	12" x 10" x 6"	18lbs
FCXLS7K-2G-O-M4-HOA-PL		460	24VAC	12/4	45 VA	6 VA	14.5-18	30A	12" x 10" x 6"	18lbs
FCXLS7K-2A-O-M01-HOA-PL		460	120VAC	1	45 VA	6 VA	14.5-18	30A	12" x 10" x 6"	18lbs
FCXLS7K-2A-O-M4-HOA-PL		460	120VAC	12/4	45 VA	6 VA	14.5-18	30A	12" x 10" x 6"	18lbs
FCXLS11K-1G-ON-M01-HOA-PL	7.5	230	24VAC	1	88 VA	9 VA	21-26	60A	16" x 12" x 8"	18lbs
FCXLS11K-1G-ON-M4-HOA-PL	7.5	230	24VAC	12/4	88 VA	9 VA	21-26	60A	16" x 12" x 8"	18lbs
FCXLS11K-1A-ON-M01-HOA-PL	7.5	230	120VAC	1	88 VA	9 VA	21-26	60A	16" x 12" x 8"	18lbs
FCXLS11K-1A-ON-M4-HOA-PL	7.5	230	120VAC	12/4	88 VA	9 VA	21-26	60A	16" x 12" x 8"	18lbs
FCXLS11K-2G-ON-M01-HOA-PL	15	460	24VAC	1	88 VA	9 VA	21-26	30A	12" x 10" x 6"	18lbs
FCXLS11K-2G-ON-M4-HOA-PL	15	460	24VAC	12/4	88 VA	9 VA	21-26	30A	12" x 10" x 6"	18lbs
FCXLS11K-2A-ON-M01-HOA-PL	15	460	120VAC	1	88 VA	9 VA	21-26	30A	12" x 10" x 6"	18lbs
FCXLS11K-2A-ON-M4-HOA-PL	15	460	120VAC	12/4	88 VA	9 VA	21-26	30A	12" x 10" x 6"	18lbs
FCXLS15K-1G-Q-M01-HOA-PL	10	200	24VAC	1	88 VA	9 VA	30-40	60A	16" x 12" x 8"	27lbs
FCXLS15K-1G-Q-M4-HOA-PL	10	200	24VAC	12/4	88 VA	9 VA	30-40	60A	16" x 12" x 8"	27lbs
FCXLS15K-1A-Q-M01-HOA-PL	10	200	120VAC	1	88 VA	9 VA	30-40	60A	16" x 12" x 8"	27lbs
FCXLS15K-1A-Q-M4-HOA-PL	10	200	120VAC	12/4	88 VA	9 VA	30-40	60A	16" x 12" x 8"	27lbs
FCXLS15K-2G-Q-M01-HOA-PL	10	230	24VAC	1	88 VA	9 VA	30-40	60A	16" x 12" x 8"	27lbs
FCXLS15K-2G-Q-M4-HOA-PL	10	230	24VAC	12/4	88 VA	9 VA	30-40	60A	16" x 12" x 8"	27lbs
FCXLS15K-2A-Q-M01-HOA-PL	10	230	120VAC	1	88 VA	9 VA	30-40	60A	16" x 12" x 8"	27lbs
FCXLS15K-2A-Q-M4-HOA-PL	10	230	120VAC	12/4	88 VA	9 VA	30-40	60A	16" x 12" x 8"	27lbs
FCXLS15K-3G-Q-M01-HOA-PL	20	460	24VAC	1	88 VA	9 VA	30-40	60A	16" x 12" x 8"	27lbs
FCXLS15K-3G-Q-M4-HOA-PL	20	460	24VAC	12/4	88 VA	9 VA	30-40	60A	16" x 12" x 8"	27lbs
FCXLS15K-3A-Q-M01-HOA-PL	20	460	120VAC	1	88 VA	9 VA	30-40	60A	16" x 12" x 8"	27lbs
FCXLS15K-3A-Q-M4-HOA-PL	20	460	120VAC	12/4	88 VA	9 VA	30-40	60A	16" x 12" x 8"	27lbs
FCXLS22K-1G-RN-M01-HOA-PL	15	200/230	24VAC	1	191 VA	17 VA	54-65	100A	20" x 16" x 8"	41lbs
FCXLS22K-1G-RN-M4-HOA-PL	15	200/230	24VAC	12/4	191 VA	17 VA	54-65	100A	20" x 16" x 8"	41lbs
FCXLS22K-1A-RN-M01-HOA-PL	15	200/230	120VAC	1	191 VA	17 VA	54-65	100A	20" x 16" x 8"	41lbs
FCXLS22K-1A-RN-M4-HOA-PL	15	200/230	120VAC	12/4	191 VA	17 VA	54-65	100A	20" x 16" x 8"	41lbs
FCXLS22K-2G-QN-M01-HOA-PL	30	460	24VAC	1	191 VA	17 VA	42-55	60A	20" x 16" x 8"	41lbs
FCXLS22K-2G-QN-M4-HOA-PL	30	460	24VAC	12/4	191 VA	17 VA	42-55	60A	20" x 16" x 8"	41lbs
FCXLS22K-2A-QN-M01-HOA-PL	30	460	120VAC	1	191 VA	17 VA	42-55	60A	20" x 16" x 8"	41lbs
FCXLS22K-2A-QN-M4-HOA-PL	30	460	120VAC	12/4	191 VA	17 VA	42-55	60A	20" x 16" x 8"	41lbs

FUSIBLE STARTER ORDERING INFORMATION/SPECIFICATION TABLE

Part Number	HP	Voltage	Coil Voltage	Enclosure NEMA Rating	Coil Inrush	Coil Holding Current	Overload Range	Fuse Block Rating	Dimensions	Weight
FCXLS37K-1G-SN-M01-HOA-PL	20/25	200/230	24VAC	1	191 VA	17 VA	64-82	100A	20" x 16" x 8"	42lbs
FCXLS37K-1G-SN-M4-HOA-PL	20/25	200/230	24VAC	12/4	191 VA	17 VA	64-82	100A	20" x 16" x 8"	42lbs
FCXLS37K-1A-SN-M01-HOA-PL	20/25	200/230	120VAC	1	191 VA	17 VA	64-82	100A	20" x 16" x 8"	42lbs
FCXLS37K-1A-SN-M4-HOA-PL	20/25	200/230	120VAC	12/4	191 VA	17 VA	64-82	100A	20" x 16" x 8"	42lbs
FCXLS37K-2G-SN-M01-HOA-PL	50	460	24VAC	1	191 VA	17 VA	64-82	100A	20" x 16" x 8"	42lbs
FCXLS37K-2G-SN-M4-HOA-PL	50	460	24VAC	12/4	191 VA	17 VA	64-82	100A	20" x 16" x 8"	42lbs
FCXLS37K-2A-SN-M01-HOA-PL	50	460	120VAC	1	191 VA	17 VA	64-82	100A	20" x 16" x 8"	42lbs
FCXLS37K-2A-SN-M4-HOA-PL	50	460	120VAC	12/4	191 VA	17 VA	64-82	100A	20" x 16" x 8"	42lbs
FCXLS45K-1G-TM-M01-HOA-PL	25/30	200/230	24VAC	1	191 VA	17 VA	78-97	100A	20" x 16" x 8"	44lbs
FCXLS45K-1G-TM-M4-HOA-PL	25/30	200/230	24VAC	12/4	191 VA	17 VA	78-97	100A	20" x 16" x 8"	44lbs
FCXLS45K-1A-TM-M01-HOA-PL	25/30	200/230	120VAC	1	191 VA	17 VA	78-97	100A	20" x 16" x 8"	44lbs
FCXLS45K-1A-TM-M4-HOA-PL	25/30	200/230	120VAC	12/4	191 VA	17 VA	78-97	100A	20" x 16" x 8"	44lbs
FCXLS45K-2G-TM-M01-HOA-PL	60	460	24VAC	1	191 VA	17 VA	78-97	100A	20" x 16" x 8"	44lbs
FCXLS45K-2G-TM-M4-HOA-PL	60	460	24VAC	12/4	191 VA	17 VA	78-97	100A	20" x 16" x 8"	44lbs
FCXLS45K-2A-TM-M01-HOA-PL	60	460	120VAC	1	191 VA	17 VA	78-97	100A	20" x 16" x 8"	44lbs
FCXLS45K-2A-TM-M4-HOA-PL	60	460	120VAC	12/4	191 VA	17 VA	78-97	100A	20" x 16" x 8"	44lbs
FCXLS55K-1G-TN-M01-HOA-PL	40	230	24VAC	1	191 VA	17 VA	90-110	200A	30" x 24" x 8"	88lbs
FCXLS55K-1G-TN-M4-HOA-PL	40	230	24VAC	12/4	191 VA	17 VA	90-110	200A	30" x 24" x 8"	88lbs
FCXLS55K-1A-TN-M01-HOA-PL	40	230	120VAC	1	191 VA	17 VA	90-110	200A	30" x 24" x 8"	88lbs
FCXLS55K-1A-TN-M4-HOA-PL	40	230	120VAC	12/4	191 VA	17 VA	90-110	200A	30" x 24" x 8"	88lbs
FCXLS55K-2G-TN-M01-HOA-PL	75	460	24VAC	1	191 VA	17 VA	90-110	200A	30" x 24" x 8"	88lbs
FCXLS55K-2G-TN-M4-HOA-PL	75	460	24VAC	12/4	191 VA	17 VA	90-110	200A	30" x 24" x 8"	88lbs
FCXLS55K-2A-TN-M01-HOA-PL	75	460	120VAC	1	191 VA	17 VA	90-110	200A	30" x 24" x 8"	88lbs
FCXLS55K-2A-TN-M4-HOA-PL	75	460	120VAC	12/4	191 VA	17 VA	90-110	200A	30" x 24" x 8"	88lbs
FCXLS75K-1G-TT-M01-HOA-PL	40/50	200/230	24VAC	1	400 VA	32 VA	140-190	200A	36" x 24" x 10"	124lbs
FCXLS75K-1G-TT-M4-HOA-PL	40/50	200/230	24VAC	12/4	400 VA	32 VA	140-190	200A	36" x 24" x 10"	124lbs
FCXLS75K-1A-TT-M01-HOA-PL	40/50	200/230	120VAC	1	400 VA	32 VA	140-190	200A	36" x 24" x 10"	124lbs
FCXLS75K-1A-TT-M4-HOA-PL	40/50	200/230	120VAC	12/4	400 VA	32 VA	140-190	200A	36" x 24" x 10"	124lbs
FCXLS75K-2G-TT-M01-HOA-PL	100	460	24VAC	1	400 VA	32 VA	140-190	200A	36" x 24" x 10"	124lbs
FCXLS75K-2G-TT-M4-HOA-PL	100	460	24VAC	12/4	400 VA	32 VA	140-190	200A	36" x 24" x 10"	124lbs
FCXLS75K-2A-TT-M01-HOA-PL	100	460	120VAC	1	400 VA	32 VA	140-190	200A	36" x 24" x 10"	124lbs
FCXLS75K-2A-TT-M4-HOA-PL	100	460	120VAC	12/4	400 VA	32 VA	140-190	200A	36" x 24" x 10"	124lbs