ALARM HORN

SC-SERIES

DESCRIPTION

The SC Series Alarm Horns provide an audible tone when an electric signal is applied. They can be used in applications when an audible alarm is needed to indicate that immediate attention is required.

SPECIFICATIONS

Supply Voltage

SC110 30-120 VAC/VDC SC628 6-28 VDC SC628A, AN 6-28 VAC/VDC

Current Rating

SC100 6-21 mA SC628 3-18 mA SC628AN 4-30 mA **SC628A** 6-23 mA

Horn Loudness Medium, 68-80 dB (AN model Loud, 80-95 dB)

Continuous

Panel Cutout Panel, cutout 1.13" (2.87 cm)

Weight


0.1 lb (0.05 Kg)
UL recognized component File# S1290 Approvals Warranty

ORDERING INFORMATION

MODEL	DESCRIPTION
SC110	Alarm horn, 120 VAC
SC628	Alarm horn, 24 VDC
SC628A	Alarm horn, 24 VAC/VDC
SC628AN	Alarm horn, 24 VAC/VDC



c**Al**°us



DESCRIPTION

The Model STB and STB-H wall-mounted strobes provide a bright, eye-catching warning light for any alarm application. The STB-H features a distinct audible signal.

FEATURES

- Wall mounted with 4" square or double-gang box
- Integral alarm horn (91 db)
- 24 VDC powered
- 15/75 candela strobe intensity
- Meets requirements of ADA4.28.3
- **UL listed**
- Xenon strobe for constant flash rate
- Strobe and horn powered separately if desired
- Jumper-selectable, continuous or temporal tone

SPECIFICATIONS

Supply Voltage 20-31 VDC (24 VDC nominal)

Current Rating

STB 80 mA at 24 VDC STB-H 136 mA at 24 VDC

Strobe Frequency 1 Hz **Horn Loudness**

104 dB max Strobe Intensity 15 (off-center) candela 75

(on-center) candela **Operating Temperature** 32° to 120°F (0° to 49°C) **Dimensions**

4.5"H x 4.56"W x 2.25"D (11.43 x 11.58 x 5.72 cm)

Weight


STB 1.0 lb (0.45 Kg) **STBH** 1.1 lb (0.5 Kg) UL Listed File S3406 **Approvals**

Warranty 3 years

WALL-MOUNTED STROBE STB, STB-H







URDERING INFORMATION	
MODEL	DESCRIPTION
STB	Wall-mounted strobe
STB-H	Wall-mounted strobe with horn

ODDEDING INFORMATION