ENCLOSURES

KELE NEMA 1 ENCLOSURES RET1 CONTROL PANEL ENCLOSURES



ENCLOSURES

DESCRIPTION

The **Kele RET1 Series** are economical NEMA 1 enclosures designed to house controls and instruments for indoor use. **RET1 Series** enclosures are furnished with a perforated steel subpanel for easy mounting of components. They come standard with a key lock in multiple sizes, and all sizes are UL-listed. The finish is powder coated, which is scratch resistant and is available in multiple colors. The door has welded butt hinges with removable pins, so the door can be detached for easy panel and component installation or field adapted to reverse the door hinge orientation. The back of the enclosure features four key-style mounting holes with dual slots, which allow the enclosure to be rotated for horizontal or vertical installation.

RET1 enclosures include threaded collar studs with nuts to install the perforated subpanel that ships with the enclosure. The perforated panel lowers labor cost through easy component alignment and mounting for a neat, finished look. Simply set the control components on the panel and attach with #7 or #8 self-tapping screws.

FEATURES


- NEMA 1 rated, UL-Listed enclosure
- Standard key lock with two keys
- 10 knockouts for 3/4 " conduit
- Removable door
- Spot welded construction, 16- or 14-gauge mild steel
- Attractive powder-coated finish in multiple colors
- Gray, powder-coated, perforated subpanel (included)



APPLICATION

- · Indoor wall mount with knockouts
- Low-voltage control components
- High-voltage control components
- Great for field panel assembly with subpanels
- Pre-built, Kele assembled, available with UL option

Construction Door	16- or 14-gauge mild steel Cold rolled with spot welded hinges	Knockouts	Ten, for 3/4" conduit (two per side, three top & bottom)
Enclosure Corners	Cold rolled and spot welded	Panel Studs	4-collar studs and nuts for perf panel
Paint	Anti-scratch powder coated	Protection	NEMA 1, IP30
Colors	,	Perf Panel	Powder-coated flanged steel 16
Standard	Brown-Tan, Gray, Dark Blue		gauge, 1/8" holes on 3/16" staggered
Special Order	Powder Blue, Orange, Green		centers
Door	Butt hinges with removable pins	Dimensions	See table below
Orientation	Left or Right, field reversible	Weight	See table below
Lock	Standard key lock, (slotted latch available)	Approvals Warranty	UL, cUL, CSA, IEC, RoHS 1 year
Mounting	Four key-style holes		•




LARGER SELECTION AND OPTIONS AVAILABLE ON KELE.COM kele.com



OSURES

ĹL.

ENCLOSURES KELE NEMA 1 ENCLOSURES RET1 CONTROL PANEL ENCLOSURES



Kele

ORDERING INFORMATION												
Part Number	Enclosure Dimensions in. (cm)			Mounting Hole Dims in. (cm)		Includes	Perforated	20				
	A -Height	B -Width	Depth	C -Horizontal Hole-Hole Spacing	D -Vertical Hole-Hole Spacing	Perforated Panel	Panel Dimensions in. (cm)	Enclosure Material	Weight Ib (kg)			
RET1-121207**-P	12 (30.5)	12 (30.5)	7 (17.8)	10.75 (27.3)	7.75 (19.7)	Yes	9.5 x 9.0 (24.1 x 22.9)	16-ga steel	14 (6.4)			
RET1-181207**-P	18 (45.7)	12 (30.5)	7 (17.8)	10.6 (26.9)	9.7 (24.6)	Yes	15.3 x 9.4 (38.9 x 23.9)	16-ga steel	18 (8.2)			
RET1-201807**-P	20 (50.8)	18 (45.7)	7 (17.8)	15.6 (39.6)	11.7 (29.7)	Yes	17.4 x 15.4 (44.2 x 39.1)	16-ga steel	26 (11.8)			
RET1-262007**-P	26 (66.0)	20 (50.8)	7 (17.8)	18.6 (47.2)	17.7 (44.9)	Yes	23.3 x 17.4 (59.2 x 44.2)	14-ga steel	35 (15.9)			
RET1-362607**-P	36 (91.4)	26 (66.0)	7 (17.8)	24.6 (62.5)	27.7 (70.3)	Yes	33.3 x 23.4 (84.6 x 59.4)	14-ga steel	63 (28.6)			
RET1-382607**-P	38 (96.5)	26 (66.0)	7 (17.8)	24.6 (62.5)	29.7 (75.4)	Yes	35.3 x 23.4 (89.7 x 59.4)	14-ga steel	67 (30.4)			
RET1-423007**-P	42 (106.7)	30 (76)	7 (17.8)	28.8 (73.2)	33.8 (85.8)	Yes	39.5 x 27.5 (100.3 x 69.9)	14-ga steel	95 (43.1)			

ACCESSORIES

MODEL RET1-LOCK RET1-KEY RET1-SLOT **DESCRIPTION** Latch with lock & two (2) replacement keys. Two replacement keys. Optional slotted (Coin) latch