


General Purpose Relay G7L

- Ideally suited for high-inrush fluid pump controls: pool/spa, water processing, emergency, chemical industry, etc.
- High-capacity, high-withstand voltage relay with no contact chattering for momentary voltage drops up to 50% of rated voltage.
- UL Class B construction standard.
- Wide-range AC-activated coil that handles 100 to 120 VAC or 200 to 240 VAC at either 50 or 60 Hz.
- Miniature size for maximum switching capacity, particularly for inductive loads.
- Flame resistant materials (UL94V-0-qualifying) used for all insulation material.
- Quick-connect, screw, PCB terminals and DIN track mounting available.
- Conforms to UL, CSA, TUV and meets IEC 950.
- Safety design with contact gap of 3 mm.
- RoHS Compliant.



Note: Accessories: E-bracket, Adapter, Front-connecting socket and Cover are sold separately.




Ordering Information

To Order: Select the part number and add the desired coil voltage rating (e.g., G7L-1A-T-CB-AC100/120).

| Type | Contact form | Model | | |
|--|--------------|------------------------|----------------|--------------|
| | | Quick-connect terminal | Screw terminal | PCB terminal |
| E bracket (see note 1) | SPST-NO | G7L-1A-T-CB | G7L-1A-B-CB | — |
| | DPST-NO | G7L-2A-T-CB | G7L-2A-B-CB | — |
| E bracket (see note 1) (with test button) | SPST-NO | G7L-1A-TJ-CB | G7L-1A-BJ-CB | — |
| | DPST-NO | G7L-2A-TJ-CB | G7L-2A-BJ-CB | — |
| Upper bracket | SPST-NO | G7L-1A-TUB-CB | G7L-1A-BUB-CB | — |
| | DPST-NO | G7L-2A-TUB-CB | G7L-2A-BUB-CB | — |
| Upper bracket (with test button) | SPST-NO | G7L-1A-TUBJ-CB | G7L-1A-BUBJ-CB | — |
| | DPST-NO | G7L-2A-TUBJ-CB | G7L-2A-BUBJ-CB | — |
| PCB mounting | SPST-NO | — | — | G7L-1A-P-CB |
| | DPST-NO | — | — | G7L-2A-P-CB |

- Note: 1. E bracket or socket must be used for mounting (part number R99-07G7L). Refer to “Accessories” section for options and part numbers.
 2. For VDE approved versions, please consult OMRON.

List of E-Bracket Mounting Models

| | | | | Mounting | E-brackets | DIN Track Mounting Adapter | Front-connecting Socket |
|-------------------------|--------------|-----------|------------------|--------------------------|---|---|--|
| Terminal | Contact form | Model | Test button | |  |  |  |
| Quick-connect terminals | SPST-NO | G7L-1A-T | - | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| | | G7L-1A-TJ | With test button | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| | DPST-NO | G7L-2A-T | - | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| | | G7L-2A-TJ | With test button | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| Screw terminals | SPST-NO | G7L-1A-B | - | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | — |
| | | G7L-1A-BJ | With test button | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | — |
| | DPST-NO | G7L-2A-B | - | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | — |
| | | G7L-2A-BJ | With test button | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | — |

Note: Accessories: E-bracket (R99-07), Adapter (P7LF-D), Front-connecting socket (P7LF-06) and Cover (P7LF-C) are sold separately.

Model Number Legend

G7L-□ - □ □ □ - □ - □ - □
 1 2 3 4 5 6 7

- | | | |
|--|--|--|
| 1. Contact form 1A:SPST-NO 2A:DPST-NO | 3. Mounting construction No symbol:E bracket type UB:Upper bracket type | 5. 80: VDE approved version (includes UL, CSA and TÜV) |
| 2. Terminal shape T:Quick-connect terminals (#250) P:PCB terminals B:Screw terminals | 4. Special functions No symbol:Without test button J:With test button | 6. CB: Class B insulation |
| | | 7. Rated coil voltage |

Accessories (Sold Separately)

Quick-connect Terminals

| Description | Model | | | | Model |
|-------------------------|--------------|-----------|----------|-----------|-----------|
| | Contact form | | | | |
| | SPST-NO | | DPST-NO | | |
| E-brackets | G7L-1A-T | G7L-1A-TJ | G7L-2A-T | G7L-2A-TJ | R99-07G7L |
| Track mounting adapter | | | | | P7LF-D |
| Front connecting socket | | | | | P7LF-06 |

Note: A socket terminal cover is supplied with the P7LF-06 socket and does not attach directly to the G7L relays. It cannot be purchased separately.

Screw Terminals

| Description | Model | | | | Model |
|------------------------|--------------|-----------|----------|-----------|-----------|
| | Contact form | | | | |
| | SPST-NO | | DPST-NO | | |
| E-brackets | G7L-1A-B | G7L-1A-BJ | G7L-2A-B | G7L-2A-BJ | R99-07G7L |
| Track mounting adapter | | | | | P7LF-D |
| Terminal Cover | | | | | P7LF-C |

Note: The P7LF-C terminal cover attaches directly to the G7L-B style relays. It is sold separately.

Specifications


Contact Data

| Load | G7L-1A-T□, G7L-1A-B□ | | G7L-2A-T□, G7L-2A-B□ | | G7L-1A-P, G7L-2A-P | |
|-------------------------|---|--------------------------------|------------------------------|--------------------------------|------------------------------|--------------------------------|
| | Resistive load (cosφ = 1) | Inductive load (cosφ = 0.4) | Resistive load (cosφ = 1) | Inductive load (cosφ = 0.4) | Resistive load (cosφ = 1) | Inductive load (cosφ = 0.4) |
| Rated load | 30 A, 220 VAC | 25 A, 220 VAC | | | 20 A, 220 VAC | |
| Contact Type | Double break | | | | | |
| Contact material | Ag alloy | | | | | |
| Carry current | 30 A | | 25 A | | 20 A | |
| Max. operating voltage | 250 VAC | | | | | |
| Max. operating current | 30 A | | 25 A | | 20 A | |
| Max. switching capacity | 6,600 VA | 5,500 VA | | | 4,400 VA | |
| Min. permissible load | 100 mA, 5 VDC (@ 60 operations / minute). Note: Do not use for switching microloads, such as signals. | | | | | |


Note: 1. P level: $\lambda_{60} = 0.1 \times 10^{-6}$ operation.
 2. When using B-series (screw) products, since the screw diameter of the contact terminal is M4, be careful that the contact current should be 20 A or less according to JET standard (electrical appliance and material control law of Japan).

Coil Internal Circuit

DC operating coil



AC operating coil



Note: 1. The ratio of rated voltage between 100 to 120 VAC are values measured on the basis of 100 VAC
 2. The AC coil is provided with a built-in full-wave rectifier. If a triac, such as an SSR, drives the G7L, the G7L may not release. Be sure to perform a trial operation with the G7L and the triac before applying them to actual use.

■ Coil Data

AC

| Rated voltage (V) | Rated current (mA) | Resistance (Ω) | Must operate | Must release | Max. voltage | Power consumption |
|-------------------|--------------------|----------------|--------------------|--------------|--------------|-------------------------|
| | | | % of rated voltage | | | |
| 12 | 142 | 75 | 75% max. | 15% min. | 110% max. | Approx. 1.70 to 2.50 VA |
| 24 | 71 | 303 | | | | |
| 50 | 34 | 1,310 | | | | |
| 100 to 120 | 17.00 to 20.40 | 5,260 | 75 volts | 18 volts | 132 volts | |
| 200 to 240 | 8.50 to 10.20 | 21,000 | 150 volts | 36 volts | 264 volts | |

DC

| Rated voltage (V) | Rated current (mA) | Resistance (Ω) | Coil inductance (H) | | Must operate | Must release | Max. voltage | Power consumption |
|-------------------|--------------------|----------------|---------------------|--------------|--------------------|--------------|--------------|-------------------|
| | | | Armature ON | Armature OFF | % of rated voltage | | | |
| 6 | 317 | 18.90 | 0.9 | 0.21 | 75% max. | 15% min. | 110% max. | Approx. 1.90 W |
| 12 | 158 | 75 | 0.37 | 0.88 | | | | |
| 24 | 79 | 303 | 1.42 | 3.54 | | | | |
| 48 | 40 | 1,220 | 6.1 | 15.3 | | | | |
| 100 | 19 | 5,260 | 21.3 | 60.0 | | | | |

- Note:** 1. The rated current and coil resistance are measured at a coil temperature of 23°C with tolerances of +15%/-20% for AC rated current and ±15% for DC coil resistance.
 2. The inductances shown above are reference values.
 3. Performance characteristic data are measured at a coil temperature of 23°C.
 4. The maximum allowable coil voltage refers to the maximum value in a varying range of operating power voltage, measured at ambient temperature 23°C.
 5. The “to” (for example “100 to 120”) represents a range of rated voltages.

■ Characteristics


| | | |
|---------------------------------------|---|--|
| Contact resistance (note 1) | | 50 mΩ max. |
| Operate time (note 2) | | 30 ms max. |
| Release time (note 3) | | 30 ms max. |
| Max. operating frequency | Mechanical | 1,800 operations/hour |
| | Electrical | 1,800 operations/hour (under rated load) |
| Insulation resistance (note 3) | | 100 MΩ min. (at 500 VDC) |
| Dielectric strength | | 4,000 VAC, min., 50/60 Hz for 1 minute between coil and contacts |
| | | 2,000 VAC, 50/60 Hz for 1 minute between contacts of same polarity |
| | | 2,000 VAC, 50/60 Hz for 1 minute between contacts of different polarity (DPST-NO type) |
| Impulse withstand voltage | | Between coil and contact: 10,000 V - JEC212 (1981) Standard Impulse Wave Type (1.20 x 50 μs) |
| Vibration | Mechanical durability | 10 to 55 Hz; 1.50 mm double amplitude |
| | Malfunction durability | 10 to 55 Hz; 1.50 mm double amplitude |
| Shock | Mechanical durability | 1,000 m/s ² (approx. 100 G) |
| | Malfunction durability | 100 m/s ² (approx. 10 G) |
| Life expectancy | Mechanical | 1,000,000 operations min. (at 1,800 operations/hour) |
| | Electrical @ 23°C | 100,000 operations min. (at 1,800 operations/hour under rated load) |
| Ambient operating temperature | | -25° to 60°C (with no icing or condensation) |
| Ambient operating humidity | | 5% to 85% RH |
| Weight | Quick-connect terminal type: approx. 90 g | |
| | PCB terminal type: approx. 100 g | |
| | Screw terminal type: approx. 120 g | |

Note: Data shown are of initial value.


- Note:** 1. Measurement conditions: 5 VDC, 1 A, voltage drop method.
 2. Measurement conditions: Rated operating voltage applied, not including contact bounce, @ 23°C.
 3. Measurement conditions: The insulation resistance was measured with a 500-VDC megohmmeter at the same locations as the dielectric strength was measured.

Engineering Data


G7L-1A-T (TJ) (TUB) (TUBJ) G7L-1A-B (BJ) (BUB) (BUBJ) Maximum Switching Power




G7L-2A-T (TJ) (TUB) (TUBJ) G7L-2A-B (BJ) (BUB) (BUBJ) Maximum Switching Power




G7L-1A-P G7L-2A-P Maximum Switching Power




Ambient Temperature vs. Operate and Release Voltage G7L-1A VAC (60 Hz)




Endurance




Endurance




Endurance




G7L-1A VDC




Ambient Temperature vs. Coil Temperature Rise G7L-1A 120 VAC (50 Hz)




G7L-1A VDC




Shock Malfunction G7L-2A-T (TUB) 100 to 120 VAC




Momentary Voltage Drop Test G7L-2A-T (TUB) 100 to 120 VAC Test Circuit



Wave resulted from test




Voltage distribution of wave e which chattering does not occur.




Characteristic variation resulted from different mounting directions

G7L-2A-T (TUB) 100 to 120 VAC


Operate time




Release time



Operate voltage



Release voltage




Note: The mounting direction A' deteriorates switching performance.

Actual Load Endurance Test


G7L-2A 100 to 200 VAC

Operate and Release voltages

N = 5




Contact resistance




Operate and Release voltages

N = 5




Contact resistance



Load conditions


• 1 φ 220 VAC



• Applied coil voltage: 100% of rated voltage

Load conditions

• 1 φ 220 VAC




• Applied coil voltage: 100% of rated voltage


G7L-2A 100 to 200 VAC

Operate and Release voltages

N = 5




Contact resistance




Operate and Release voltages

N = 5




Contact resistance



Load conditions


• 1 φ 220 VAC



• Applied coil voltage: 75% of rated voltage

Load conditions

• 1 φ 220 VAC



• Applied coil voltage: 75% of rated voltage

Applications

- Compressors for package air conditioners and heater switching controllers
- Switching controllers for power tools or motors
- Power controllers for water heaters
- Power controllers for dryers
- Lamp control, motor drivers, and power supply switching in copy machines, facsimiles, and other office equipment
- Lighting controllers
- Power controllers for packers or food processing equipment
- Magnetron control in microwaves
- Power controllers for Uninterruptible Power Supplies (UPS)

Dimensions



Unit: mm (inch)

■ Relays


Quick-Connect Terminal Models

E-bracket Mounting*

G7L-1A-T






Terminal arrangement/ Internal connections (Top view)



(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.




G7L-2A-T



(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.




G7L-1A-TJ (with Test Button)



(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.


G7L-2A-TJ (with Test Button)



(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.


Mounting holes




* E brackets are sold separately

Adapter Mounting*

G7L-1A-T





Terminal arrangement/ Internal connections (Top view)



(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.


G7L-2A-T





(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.

Mounting holes





G7L-1A-TJ (with Test Button)



(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.

G7L-2A-TJ (with Test Button)




(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.


* The DIN Track Mounting Adapter and DIN tracks are sold separately. The adapter can be track-mounted or screw-mounted.

Front-connecting Socket Mounting*

G7L-1A-T





Terminal arrangement/ Internal connections (Top view)



(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.


G7L-2A-T





(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.

Mounting holes





G7L-1A-TJ (with Test Button)



(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.

G7L-2A-TJ (with Test Button)





(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.


* The Front-connecting Socket and DIN tracks are sold separately. The socket can be track-mounted or screw-mounted.

Upper Bracket Mounting

G7L-1A-TUB






Terminal arrangement/ Internal connections (Top view)



(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.

G7L-2A-TUB




(No coil polarity)




Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.

Mounting holes

Two, 4.5-dia. hole or
M4 tapped holes






G7L-1A-TUBJ (with Test Button)



(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.

G7L-2A-TUBJ (with Test Button)






(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.


Screw Terminal Models

E-bracket Mounting*

G7L-1A-B







Terminal arrangement/ Internal connections (Top view)



(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.


G7L-2A-B







(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.

Mounting holes







G7L-1A-BJ (with Test Button)



(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.

G7L-2A-BJ (with Test Button)




(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.


* E brackets are sold separately

Adapter Mounting*

G7L-1A-B





Terminal arrangement/ Internal connections (Top view)



(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.


G7L-2A-B





(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.

Mounting holes





G7L-1A-BJ (with Test Button)



(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.

G7L-2A-BJ (with Test Button)





(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.


* The DIN Track Mounting Adapter and DIN tracks are sold separately. The adapter can be track-mounted or screw-mounted.

Upper Bracket Mounting

G7L-1A-BUB






Terminal arrangement/ Internal connections (Top view)



(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.

G7L-2A-BUB




(No coil polarity)




Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.

Mounting holes

Two, 4.5-dia. hole or M4 tapped holes






G7L-1A-BUBJ (with Test Button)



(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.

G7L-2A-BUBJ (with Test Button)





(No coil polarity)


Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.

PCB Terminal Models

G7L-1A-P



Terminal arrangement/ Internal connections (Top view)




(No coil polarity)




Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.

PCB Mounting holes (Bottom view)

Tolerance ± 0.1 mm



G7L-2A-P




(No coil polarity)

Note: Refer to "Coil Internal Circuit" for the coil internal connection diagram.


PCB Mounting holes (Bottom view)

Tolerance ± 0.1 mm




Accessories (Sold Separately)


E bracket R99-07G7L




Mounting holes (Bottom view)




Adapter P7LF-D




Mounting holes (Bottom view)



Front connecting socket P7LF-06




Mounting holes (Bottom view)



- Note:**
1. To protect against electric shock, a socket terminal cover is supplied with the P7LF-06 socket. It cannot be purchased separately.
 2. The P7LF-D and P7LF-06 are panel or track mountable.
 3. The P7LF-D is for use with quick connect or screw models that accept the E-bracket.
 4. The P7LF-06 is for use with quick connect models that accept the e-bracket.

Cover P7LF-C




Note: P7LF-C cover attaches directly to G7L-B style relays. To protect against electric shock, use the P7LF-C on G7L-B terminals.

Mounting track

PFP-100N, PFP-50N
(Conforming to EN 50022)

PFP-100N2
(Conforming to EN 50022)



* The figure in parenthesis is for PFP-50N.

Note: 1. It is recommended that a panel thickness of 1.60 to 2.00 mm (0.06 to 0.08 in) be used.

2. L = Length


PFP-100N L = 1 m (39.00 in)

PFP-50N L = 50 cm (19.60 in)

PFP-100N2 L = 1 m (39.00 in)


End plate

PFP-M



Spacer

PFP-S



■ Approvals

• A variety of Safety Standard approved products for standard models.

UL approval (File No. E41643)

| Model | Coil ratings | Contact ratings | Number of test operations |
|--|-------------------------------|------------------------------|---------------------------|
| | | SPST-NO | |
| G7L-1A-T□ G7L-1A-B□ G7L-1A-P G7L-2A-T□ G7L-2A-B□ G7L-2A-P | 12 to 240 VAC 6 to 220 VDC | 30 A, 277 VAC (RES) 40°C | 100,000 |
| | | 1.5 kW, 120 VAC (T) 40°C | 6,000 |
| | | 1.5 HP, 120 VAC 40°C | 1,000 |
| | | 3 HP 277 VAC 40°C | 100,000 |
| | | 20 FLA/120 LRA, 120 VAC 40°C | 30,000 |
| | | 17 FLA/102 LRA, 277 VAC 40°C | 30,000 |
| | | TV-10, 120 VAC 40°C | 25,000 |

CSA approval (File No. LR31928)

| Model | Coil ratings | Contact ratings | Number of test operations |
|--|-------------------------------|--------------------------------|---------------------------|
| | | SPST-NO | |
| G7L-1A-P | 12 to 240 VAC 6 to 220 VDC | 2.4 kW, 120 VAC (T) 40°C | 6,000 |
| | | 1.5 HP, 120 VAC (T) 40°C | 1,000 |
| | | 3 HP 277 VAC 40°C | 100,000 |
| | | 20.5 FLA/105 LRA, 120 VAC 85°C | 100,000 |
| | | TV-10, 120 VAC 40°C | 25,000 |
| G7L-1A-T□ G7L-1A-B□ G7L-2A-T□ G7L-2A-B□ G7L-2A-P | 12 to 240 VAC 6 to 220 VDC | 30 A, 277 VAC (RES) 40°C | 100,000 |
| | | 2.4 kW, 120 VAC (T) 40°C | 6,000 |
| | | 1.5 HP, 120 VAC 40°C | 1,000 |
| | | 3 HP 277 VAC 40°C | 100,000 |
| | | 20.5 FLA/105 LRA, 120 VAC 85°C | 100,000 |
| | | TV-10, 120 VAC 40°C | 25,000 |

Reference

UL Approved Type

- UL508 Industrial Control Devices
- UL1950 Information processing equipment
(Including office equipment)

CSA Approved Type.....

- CSA C22.2 No.1, 14
Industrial Control Devices
- CSA C22.2 No.950 Information processing equipment
(Including office equipment)

TÜV EN/IEC Standard Approved Type.....

- EN61810-1 Relay
- EN60950 Information processing equipment
(Including office equipment)
- IEC950 Information processing equipment
(Including office equipment)

VDE recognized type (License no. 1530 UG)

Note: 1. Please consult OMRON for details of VDE approvals.

2. The G7L relay conforms to the following standards:

Electrical safety: DIN IEC 255 Teil 1-00/DIN VDE 0435 Teil 201/05. 83
DIN VDE 0435 Teil 201 A1/05. 90
DIN IEC 255 Teil 0-20/DIN VDE 0435 Teil 120/10. 81
DIN EN 60 950/VDE 0805/11. 93

EMC: prEN 50082-2, EN 55022

3. The rated values approved by each of the safety standards (e.g., UL and CSA) may be different from the performance characteristics individually defined in this catalog.
4. In the interest of product improvement, specifications are subject to change.
5. Suffix T130 rated at 130°C
6. Pollution degree 3, Material Group II & III.
7. CE marking is provide only on non-PCB terminal versions.

EN/IEC, TÜV Approval (File No. R50059083)

| Model | Coil ratings | Contact ratings | Approved switching operations |
|-----------|--|---|-------------------------------|
| | | SPST-NO | |
| G7L-1A-B□ | 6, 12, 24, 48, 100, 110, 200, 220 VDC 12, 24, 50, 100 to 120, 200 to 240 VAC | 30 A, 250 VAC ~ (cosφ = 1) 60°C 25 A, 250 VAC ~ (cosφ = 0.4) 60°C 30 A, 120 VAC ~ (cosφ = 0.4) 60°C | 50,000 |
| G7L-2A-B□ | | DPST-NO 25 A, 277 VAC ~ (cosφ = 1) 60°C 25 A, 277 VAC ~ (cosφ = 0.4) 60°C | 50,000 |
| G7L-1A-T□ | | SPST-NO 25 A, 240 VAC ~ (cosφ = 1) 60°C 25 A, 240 VAC ~ (cosφ = 0.4) 60°C 25 A, 277 VAC ~ (cosφ = 1) 60°C 25 A, 277 VAC ~ (cosφ = 0.4) 60°C | 50,000 |
| | | DPST-NO 25 A, 240 VAC ~ (cosφ = 1) 60°C 25 A, 240 VAC ~ (cosφ = 0.4) 60°C 25 A, 277 VAC ~ (cosφ = 1) 60°C 25 A, 277 VAC ~ (cosφ = 0.4) 60°C | 50,000 |
| G7L-2A-T□ | | SPST-NO 20 A, 240 VAC ~ (cosφ = 1) 60°C 20 A, 240 VAC ~ (cosφ = 0.4) 60°C 25 A, 277 VAC ~ (cosφ = 1) 60°C 25 A, 277 VAC ~ (cosφ = 0.4) 60°C | 50,000 |
| G7L-1A-P | | DPST-NO 20 A, 240 VAC ~ (cosφ = 1) 60°C 20 A, 240 VAC ~ (cosφ = 0.4) 60°C 25 A, 277 VAC ~ (cosφ = 1) 60°C 25 A, 277 VAC ~ (cosφ = 0.4) 60°C | 50,000 |
| | | DPST-NO 20 A, 240 VAC ~ (cosφ = 1) 60°C 20 A, 240 VAC ~ (cosφ = 0.4) 60°C 25 A, 277 VAC ~ (cosφ = 1) 60°C 25 A, 277 VAC ~ (cosφ = 0.4) 60°C | 50,000 |

Precautions

■ Correct Use

Handling

To preserve initial performance, do not drop or otherwise subject the power relay to shock.

The case is not designed to be removed during normal handling and operation. Doing so may affect performance.

Use the power relay in a dry environment free from excessive dust, SO₂, H₂S, or organic gas.

Do not allow a voltage greater than the maximum allowable coil voltage to be applied continuously.

Do not use the power relay outside of specified voltages and currents.

Do not allow the ambient operating temperature to exceed the specified limit.

Installation

Although there are not specific limits on the installation site, it should be as dry and dust-free as possible.

Using in an atmosphere of high humidity and corrosive gas may deteriorate its performance characteristic caused by condensation or corrosive products, resulting in failure or burn damage of the Relay.

PCB terminal-equipped relays weigh approximately 100 g. Be sure that the PCB is strong enough to support them. We recommend dual-side through-hole PCBs to reduce solder cracking from heat stress.

Relays with test buttons must be mounted facing down. Be careful not to touch the test button accidentally. Doing so may turn on the contact.

Be sure to use the test button for test purposes only (with test-button models). The test button is used for Relay circuit tests, such as circuit continuity tests. Do not attempt to switch the load with the test button.

Soldering PCB Terminals

Do not perform automatic soldering, but solder manually.

Do not wash down the entire Relay because it does not have an airtight construction.

Connecting

Refer to the following table when connecting a wire with a crimp style terminal to the G7L.

| | Screw Terminals | Front Connecting Socket |
|----------------|-----------------|-------------------------|
| Coil | | |
| Contact | | |

Allow suitable slack on leads when wiring and do not apply excessive force to the terminals.

Tightening torque;

Coil: 0.78 to 1.18 N·m

Contacts: 0.98 to 1.37 N·m

When connecting with screws, if the screws are not sufficiently tightened, the lead wire can become detached and may lead to abnormal heating or fire caused by faulty contact.

Do not apply excessive force when mounting or dismantling the faston receptacle. Insert and remove terminals carefully, one at a time. Do not insert terminals at an angle, or insert / remove multiple terminals at the same time.

Do not connect to the terminals by soldering. Use #250 faston or positive-lock connectors;

| Type | Receptacle Terminals* | Positive Housing |
|---------------------------------|---|--|
| #250 terminals (width: 6.35 mm) | AMP 170333-1 (170327-1) AMP 170334-1 (170328-1) AMP 170335-1 (170329-1) | AMP 172076-1 natural color AMP 172076-4 yellow AMP 172076-5 green AMP 172076-5 blue |

*the numbers shown in parentheses are for air-feeding.

- Note:** 1. The current should be 25A when using receptacle terminals.
2. Use receptacle terminals or positive housing for cable wiring.

Mounting

Top Bracket Type

Mounting torque; 0.98 N·m

Tighten with to M4 screws when mounting.

DIN Track Mounting Adapter and Front-Connecting Socket

The DIN Track Mounting Adapter and Front-connecting Socket can be mounted on the G7L with just one hand and dismantled with ease using a screwdriver.

To support the G7L mounted on a DIN Track Mounting Adapter or Front-connecting Socket, use the PFP-M End Plate. Put the End Plate onto the DIN Track Mounting Adapter or Front-connecting Socket so that the surface mark of the End Plate faces upwards. Then tighten the screw of the End Plate securely with a screwdriver.

Screw Mounting


Screw-mount the DIN Track Mounting Adapter or Front-connecting Socket securely after opening screw mounting holes on them.

When cutting or opening holes on the panel after the Front-connecting Socket is mounted, take proper measures so that the cutting chips will not fall onto the Relay terminals. When cutting or opening holes on the upper part of the panel, mask the Front-connecting Socket properly with a cover.

Operating Coil

- As a rule, either a battery or a DC power supply with a maximum 5% ripple is used for the operating voltage for DC relays. Before using a rectified AC supply, confirm that the ripple is not greater than 5%. Ripple greater than this can lead to variations in the operating and reset voltages.

As excessive ripple can generate beats, the insertion of a smoothing capacitor is recommended as shown below.



- When driving a transistor, check the leakage current and connect a bleeder resistor if necessary.
- Momentary voltage drops on coil input voltage should not exceed one second duration after contact mating with no shock or vibration.



All sales are subject to Omron Electronic Components LLC standard terms and conditions of sale, which can be found at http://www.components.omron.com/components/web/webfiles.nsf/sales_terms.html

ALL DIMENSIONS SHOWN ARE IN MILLIMETERS.
To convert millimeters into inches, multiply by 0.03937. To convert grams into ounces, multiply by 0.03527.

OMRON[®]

**OMRON ELECTRONIC
COMPONENTS LLC**

55 E. Commerce Drive, Suite B
Schaumburg, IL 60173

847-882-2288

OMRON ON-LINE

Global - <http://www.omron.com>

USA - <http://www.components.omron.com>

Cat. No. J055-E-07

07/13

Specifications subject to change without notice

Printed in USA