

Functional Devices, Inc. •

p: 800.888.5538


f: 765.883.7505 •

www.functionaldevices.com •


sales@functionaldevices.com

# **RIBMNA1D0**

2.75" Track Mount Manual Analog Override Switch + Monitor with 24 Vac/dc Power Input



#### **Legend for Selecting Output for Jumpers**



15 Vdc 📲 📲 📲

## **Manual Analog Override Switch**





## **Specifications**

Operating Temperature: -30 to 140° F

Humidity Range: 5 to 95% (noncondensing)
Dimensions: 2.450" x 2.750" x 1.270"

Track Mount: 2.750", See MT212 Series on page 142

MT212 Mounting Track Sold Separately Input Voltage: 24 Vac/dc

0-10 Vdc, 400  $\Omega$  Min. 0-15 Vdc, 1 k $\Omega$  Min. 0-20mA dc, 500  $\Omega$  Max.

Feedback Contact: 2A Max. @ 24 Vac/dc

#### Notes:

- Set the jumpers according to your input signal (Analog signal from the controller.) Example: When controlling a damper with 0-10 Vdc, the jumpers need to be in position for the 0-10 Vdc override range. If the LED range does not match your analog scale, ensure the jumpers are set for the proper range.
- Feedback contact closed when switch is in Manual position, open when switch is in Auto position.

- Provides manual override if controller does not support override capability
- Allows you to manually make adjustments to your end device remotely instead of at your control panel
- Sends override status back to controller via feedback
- Multi-range analog output