

VAISALA RH / TEMPERATURE METER HM40A1AB

DESCRIPTION

This handheld, pocket-sized **Vaisala Model HM40A1AB RH/ Temperature Meter** provides a fast and convenient way to accurately spot-check relative humidity and temperature.

FEATURES

- *Measurement of humidity, temperature, dewpoint, wet bulb and enthalpy*
- *Large graphical display*
- *Multiple languages*
- *2 x AA 1.5 Volt Battery*
- *Belt clip*


VAISALA


HM40A1AB

SPECIFICATIONS

Supply Voltage	2 x AA Alkaline 1.5 Volt Battery
Sensor Response Time	17 seconds
Sensor Type	
Humidity	HUMICAP® 180R
Temperature	PT 1000 RTD
Humidity Accuracy	±1.5% (0% to 90% RH) ±2.5% (90% to 100% RH)
Humidity Range	0% to 100% RH
Temperature Accuracy	± 0.36°F (± 0.22°C)

Temperature Range	14° to 140°F (-10° to 60°C)
Display	LCD
Dimensions	9.4"L x 2.8"W x 1.7"D (23.8 x 7.2 x 4.4 cm)
Weight	0.6 lb (0.3 kg)
Approvals	CE, NIST Traceable certificate included
Warranty	1 year

ORDERING INFORMATION

MODEL
HM40A1AB

DESCRIPTION
RH / Temperature meter with F/C reading

EXTECH VIDEO BORESCOPE BR200

DESCRIPTION

The Extech **BR200** video borescope inspection camera is ideal for inspecting hard to reach spaces. Battery-powered, light weight, and able to light up dark places. This easy-to-use tool can capture images, date/time stamp them, and download to a PC.


EXTECH
INSTRUMENTS
A FLIR COMPANY


BR200

FEATURES

- *Transfer Video and images to your PC via the microSD card or USB cable (included) and viewed using Windows® Media Player*
- *NTSC or PAL operation*
- *Mini water-proof (IP67) camera for high resolution viewing*
- *Glare-free, close-up field of view*

SPECIFICATIONS

CAMERA	
Supply Voltage	4 x AA Alkaline 1.5 Volt Battery
Resolution	712 x 486 px (NTSC)
Transmission Frequency	2.4GHz
Transmission Range	32' (10m) unobstructed view
Focus Distance	5.9" to 9.8" (15 to 25cm)
Working length	39" (1m)
Minimum Bend Radius	2.36" (6 cm)
Handle Dimensions	7.3" x 5.7" x 1.6" (18.6 x 14.5 x 4.1 cm)
Weight	1.17 lbs
MONITOR	
LCD Screen Type	3.5" TFT
Screen Resolution	320 x 240 px
Video Resolution	960 x 240 (AVI format)
Image Resolution	640 x 480 (JPEG format)
Video Output Level	0.9 to 1.3V @ 75Ω
Frame Rate	10, 15, 20, 25, 30FPS
Dimensions	3.9" x 2.7" x 1" (10.0 x 7.0 x 2.5 cm)
Operating Time	1.5 hours
Charge Time	3 hours
Weight	0.30 lbs
Warranty	1 year

ORDERING INFORMATION

Model	Description
BR200	Flexible video borescope with 39" cable
BR200-EXT	38" Extension cable