


## THERMOWELLS

# Thermowells for Building Automation Temperature Sensors



Fabricated (Welded) Thermowell

1-1/8 HEX [28.55] INSERTION\_ LENGTH 1-3/4 [45.21] WELDED (SEALED) 1/2" NPSM 1/2" NPT OR BSPT THREAD INTERNAL THREAD



1-3/4

[44.45] [6.35]

R 1/8

Ø1/4

[7.11]

The Series TE-TNS Stainless Steel Thermowells are used to separate the instrument from the surrounding media. When used with the Series TE and TE-I Immersion Temperature Sensors, further protection is offered from aggressive media, high pressures, and flow rates while allowing for quick and easy installation of temperature

resides, and now rates while allowing for quick and easy installation of temperature sensors without having to drain process media.

Thermowells are offered in both 304 and 316 stainless steel allowing for superior corrosion resistance. Fabricated, or welded, thermowells are constructed from a tube that is closed at the tip by a welded solid tip. Solid-machined thermowells are manufactured from barstock.

#### **FEATURES/BENEFITS**

- Configurable materials and sizes
   Fabricated (welded) or machined construction
   1/2" or 3/4" NPT process connections

- APPLICATIONS

   Building automation

   Chiller or boiler loops
- · Chemical industry or process

O.	10		111	Jui	
tρ	ch	ın	0	loa	v

MODEL CHART						
Example	TE-TNS	-N	9	5N	-14	TE-TNS-N095N-14
Series	TE-TNS					Stainless steel thermowell
Thread Type		N				NPT
Length			2.5 04 06 09 12 18			2.5" 4" 6" 9" 12" 18"
Material & Construction				3N 4N 5N		304 SS fabricated (welded) 304 SS machined 316 SS machined
Connection (Internal & External)					00 12 14	1/2" NPSM / 1/2" NPT   1/2" NPT / 3/4" NPT   1/4" NPT / 1/2" NPT

### **SPECIFICATIONS**

Maximum Pressure: Fabricated: 140 psi; Machined: 304 SS: 3700 psi; 316 SS:

2X BREAK Ø1-1/8 [28.55] X 30°

SEE BELOW FOR-

THREAD DETAIL 3/4 [19.05]

5500 psi.

Maximum Temperature: Fabricated: 1000°F (538°C); Machined: 1200°F (648°C).

Construction: Fabricated (welded) or machined model specific.

MODEL CHART							
MODEL CHART							
Madal			0	Connection			
Model				(Internal/External)			
TE-TNS-N044N-14	304 SS	4"	Machined	1/4" NPT / 1/2" NPT			
TE-TNS-N044N-12	304 SS	4"	Machined	1/2" NPT / 3/4" NPT			
TE-TNS-N064N-14	304 SS	6″	Machined	1/4" NPT / 1/2" NPT			
TE-TNS-N064N-12	304 SS	6″	Machined	1/2" NPT / 3/4" NPT			
TE-TNS-N094N-14	304 SS	9″	Machined	1/4" NPT / 1/2" NPT			
TE-TNS-N094N-12	304 SS	9″	Machined	1/2" NPT / 3/4" NPT			
TE-TNS-N124N-14	304 SS	12"	Machined	1/4" NPT / 1/2" NPT			
TE-TNS-N124N-12	304 SS	12"	Machined	1/2" NPT / 3/4" NPT			
TE-TNS-N045N-14	316 SS	4"	Machined	1/4" NPT / 1/2" NPT			
TE-TNS-N045N-12	316 SS	4"	Machined	1/2" NPT / 3/4" NPT			
TE-TNS-N065N-14	316 SS	6″	Machined	1/4" NPT / 1/2" NPT			
TE-TNS-N065N-12	316 SS	6″	Machined	1/2" NPT / 3/4" NPT			
TE-TNS-N095N-14	316 SS	9″	Machined	1/4" NPT / 1/2" NPT			
TE-TNS-N095N-12	316 SS	9″	Machined	1/2" NPT / 3/4" NPT			
TE-TNS-N125N-14	316 SS	12"	Machined	1/4" NPT / 1/2" NPT			
TE-TNS-N125N-12	316 SS	12"	Machined	1/2" NPT / 3/4" NPT			
TE-TNS-N253N-00	304 SS	2.5"	Fabricated	1/2" NPSM / 1/2" NPT			
TE-TNS-N043N-00	304 SS	4″	Fabricated	1/2" NPSM / 1/2" NPT			
TE-TNS-N063N-00	304 SS	6″	Fabricated	1/2" NPSM / 1/2" NPT			
TE-TNS-N083N-00	304 SS	8″	Fabricated	1/2" NPSM / 1/2" NPT			
TE-TNS-N123N-00	304 SS	12"	Fabricated	1/2" NPSM / 1/2" NPT			
TE-TNS-N183N-00	304 SS	18"	Fabricated	1/2" NPSM / 1/2" NPT			